


MOULDED CASE CIRCUIT BREAKERS (MCCB)

SAFE



	114-004-3040	114-004-3050	114-004-3063	114-004-3100	114-004-3125	114-004-3160	114-004-3200	114-004-3250	114-004-3400	114-004-3630
Rated Current (A)	: 40A	50A	63A	100A	125A	160A	200A	250A	400A	630A
Poles	: 3 Pole	3 Pole	3 Pole	3 Pole	3 Pole	3 Pole	3 Pole	3 Pole	3 Pole	3 Pole
Instantaneous tripping type	: C	C	C	C	C	C	C	C	C	C
Rated short-circuit breaking capacity (kA)	: 20kA	20kA	20kA	35kA	35kA	35kA	35kA	35kA	35kA	35kA
Rated working voltage(V)	: 400V	400V	400V	400V	400V	400V	400V	400V	400V	400V
Sizes (mm)	: A:135 B:78 C:74	A:135 B:78 C:74	A:135 B:78 C:74	A:150 B:92 C:69	A:150 B:92 C:69	A:165 B:101 C:86	A:165 B:101 C:86	A:165 B:101 C:86	A:257 B:150 C:106.5	A:270 B:182 C:110

Technical Drawing



Applications

- Industrial areas
- Commercial uses

