



### Main

Range	Asfora
Product or component type	Socket-outlet
Outlet standard description	Side earth
Outlet poles configuration	2P + E
Device presentation	Mechanism with fixing frame
Colour tint	Anthracite
Type of packing	Flow-pack

### Complementary

Socket number	1
Device mounting	Flush
Power range	3680 W
Rated current	16 A at 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 cable(s) 2.5 mm <sup>2</sup>
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13.0 Mm
Material	ABS + PC: central plate
Surface finish	Painted
Conductor material	Copper
Fixing mode	Screws or claws 51...69 mm
Height	71 Mm
Width	71 Mm
Depth	42 Mm
Projecting depth	10 Mm
Quantity per set	1
Net weight	0.068 Kg

### Environment

Standards	IEC 60884-1
Product certifications	TSE VDE
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 Cm
Package 1 Width	7.0 Cm
Package 1 Length	7.0 Cm
Package 1 Weight	69.0 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 Cm
Package 2 Width	18.5 Cm
Package 2 Length	27.5 Cm
Package 2 Weight	764.25 G
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30.0 Cm
Package 3 Width	40.0 Cm
Package 3 Length	60.0 Cm
Package 3 Weight	9.726 Kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product Life Status : **Commercialised**